

www.mh-partners.com Portable Container Tilters

Standard Non-Straddle and Straddle Models

Positions wire baskets and large tote boxes containing components within sight and easy reach of production workers.

- **Capacity:** 2000 and 4000 lbs. at a 24" load center
- **Degree of tilt:** 0° – 90°
- **Motor:** internally mounted, 1 h.p. D.C.
- **Battery:** leak-proof, 12 volt, 60 amp and 72 amp gel cell
- **Battery charger:** external, 10 amp is standard
- **Pallet truck type forks:** length 42", width 6¼", thickness 2", O.D. 26½" and I.D. 14" (backplate 27"W x 30"H)
- **Rear casters:** 8" x 2" nylon; **Load wheels:** 3" nylon for non-straddle models and 5" x 2" phenolic for straddle models.
- **Hand held push button control:** 8' coil cord is standard (foot control optional)

| Model Number | Capacity (lbs.) | Degree of Tilt | Fork O.D. | Overall Size | Raise Time | Ship. Wgt | Price |
|--|-----------------|----------------|-----------|--------------|------------|-----------|-------|
| PT Series – Standard Non-Straddle | | | | | | | |
| PT-20 | 2000 | 0°-90° | 26½" | 34"W-62"L | 26 sec | 725 | - |
| PT-40 | 4000 | 0°-90° | 26½" | 34"W-62"L | 30 sec | 740 | - |
| PTS 42 Series – 42" I.D. Straddle | | | | | | | |
| PTS42-20 | 2000 | 0°-90° | 26½" | 48"W-62"L | 26 sec | 765 | - |
| PTS42-40 | 4000 | 0°-90° | 26½" | 48"W-62"L | 30 sec | 785 | - |
| PTS 50 Series – 50" I.D. Straddle | | | | | | | |
| PTS50-20 | 2000 | 0°-90° | 26½" | 56"W-62"L | 26 sec | 780 | - |
| PTS50-40 | 4000 | 0°-90° | 26½" | 56"W-62"L | 30 sec | 800 | - |



Options: 115 volt A.C. motor, air motors, stationary units available – consult factory.
Note: 2000 lbs. capacity has 60 amp battery; 4000 lbs. capacity has 72 amp battery.