

Post Lift Tables at www.mh-partners.com

Here's a simple, low-cost solution to lifting, work positioning, and transporting problems. Top is raised and lowered by central lifting cylinder. Guide posts provide stability; 2 posts for lighter capacity and 4 posts for heavier capacity and 4 posts for 2000 lbs. and over. Manual units have a foot operated hydraulic pump and tip toe release. Battery units use an electro-mechanical, screw drive linear actuator powered by 12 volt, 35 amp gel cell type, leak-proof and maintenance free battery. 10 amp battery charger is standard. All units have a special contoured dropped base for maximum lowered height.

- **Battery and Manually Operated**
- **Capacities of 500 to 4000 lbs.**

Foot Pedal Hydraulic Pump

Model No.	Capacity (lbs)	Lift Height	Low'd Height	Travel	Platform Size	Ship. Wgt	Price
P18-5	500	49"	31"	18"	20"W x 30"L	185	-
P18-10	1000	49"	31"	18"	20"W x 30"L	190	-
P18-20	2000	49"	31"	18"	24"W x 36"L	200	-
P18-30	3000	49"	31"	18"	24"W x 36"L	205	-
P18-40	4000	49"	31"	18"	24"W x 36"L	215	-

Electromechanical, Battery Operated

Model No.	Capacity (lbs)	Lift Height	Low'd Height	Travel	Platform Size	Ship. Wgt	Price
BP18-5	500	52"	34"	18"	20"W x 30"L	215	-
BP18-10	1000	52"	34"	18"	20"W x 30"L	270	-
BP18-20	2000	52"	34"	18"	24"W x 36"L	330	-

AC electric (115/1/60) power (in lieu of battery).

Four posts for heavy capacity

Two posts for lighter capacity

Hand held control with 10' cord

10 amp battery charger (standard)

Contoured base for maximum lowered height

12 volt gel cell battery

Floor saving 5" phenolic wheels



Options:

Low profile models with 25" lowered height, 37" raised height (12" travel).

Hydraulic Lift Tables

These hydraulic tables provide lifting of loads to 2000 lbs. with effortless foot pump operation. 24"W x 36"L platform, dual floor locks, welded construction, cam follower bearings, and heavy-duty hydraulic system are standard.

- **Unique design** allows access to hard-to-reach areas.

Phenolic wheels

Foot operated



Options and Accessories:

Steel Wheels

Rubber Wheels (1000 lb. capacity only)

Turntables and **Conveyer Tops**: see Scissor Lift options.

Model No.	Capacity (lbs)	Lift Height	Low'd Height	Travel	Ship. Wgt	Price
PL48 (Std. Profile)	2000	48"	30"	18"	315	-
PL36 (Low Profile)	2000	36"	24"	12"	295	-
PL60 (High Profile)	2000	60"	36"	24"	335	-

Mechanical Elevating Tables

Four (4) self-locking Acme Screw thread posts put the table top at precisely the right height. For raising and lowering, two-speed crank studs are located at both ends of the table.

- **Mechanically operated** for precise positioning and positive holding.

Options:

Smaller and larger size tables available (consult factory).
Modifications to lifting heights available (consult factory).

18" travel

Acme thread posts

3 work storage areas



Floor lock

Phenolic wheels

Model No.	Capacity (lbs)	Lift Height	Low'd Height	Table Size	Ship. Wgt	Price
P2436	2000	42"	24"	24" x 36"	300	-
P2448	2000	42"	24"	24" x 48"	360	-
P3036	2000	42"	24"	30" x 36"	345	-
P3048	2000	42"	24"	30" x 48"	425	-